



Standard U marking

### Technical Data:

|                         |  |
|-------------------------|--|
| Basic Frame             | Aluminum Section                             |
| Construction            | CKD Type.                                    |
| Std. Equipment Mounting | DIN Std. M6 Tapped Hole                      |
| Standard Finish         | Powder Coated                                |
| Standard Colour         | Grey & OFF White Or Black                    |
| Standard Mounting       | Grouting                                     |
| Rack Standard           | Conforms to DIN 41494 or equivalent standard |
| Static Load             | 1500 Kg                                      |

1U = 44.45 mm

Note: Other models can be manufactured on request.

### Features

- Made of Heavy Aluminum Sections
- Open architecture for easy access to cable and unrestricted air flow
- Adjustable depth 650 to 850 mm to suite site conditions
- Standard U marking for fast equipment mounting
- Static Load 1500Kg
- Ability to add NetRack cable organizers for cable organizing and routing
- DIN Std M6 Tapped holes.

### Model Matrix & Dimensions

| Open Rack | H    | .h  | W   | .w  |
|-----------|------|-----|-----|-----|
| 22U       | 1125 | 22U | 514 | 450 |
| 36U       | 1747 | 36U | 514 | 450 |
| 42U       | 2013 | 42U | 514 | 450 |
| 45U       | 2147 | 45U | 514 | 450 |