

OVERVIEW

NRFS -4 Post Series, **Rigid racks designed for Combined Networking & Equipment Mounting, Server or for lab application which requires 4 post frame with low, medium or high density cable management.** The Racks manufactured out of steel sheet punched, formed, welded and Powder coated with highest quality standards under stringent ISO 9001 2008 Manufacturing & Quality management system to ensure highest quality product.

Standard for Racks configuration will be welded rigid frame with 4 no Pillars of 14 Gauge steel sheet 5 folded profile welded to top and bottom Cover additionally supported depth wise by welding 6 No. depth rail 4 folded 75 mm 14 Gauge profile with optional side panels. Recommended to grout on floor with plinth alternatively, free standing 4 No. casters wheels (2 No. with brakes & 2 No without) & Levelers.

Available in 44 RU 800 and 1000 depth configurations and 600 width configurations.



Features

- Conforms to DIN 41494 or Equivalent EIA/ISO/EN/CEA Standard
- Adjustable mounting depth
- 4 No Adjustable. 19" verticals with Punched 10mm Square Hole and Universal 12.7mm -15.875mm-15.875mm alternating hole pattern offers greater mounting flexibility, maximizes usable mounting space.
- Numbered U positions
- Universal 25mm Pitch Holes for ETSI Standard Racks
- State-of-the-art manufacturing methods provide the best product quality and fastest delivery in the industry
- 100% assured compatibility with all equipments conforming to DIN 41494 (General industrial standard for equipments)
- Powder coated finish with Seven tank pretreatment process meeting ASTM standard
- Grounding & Bonding Options

Technical Data:

Basic Frame	Steel folded
Construction	Welded
Top & Bottom Cover	Welded to frame
Mounting Angle	Formed Steel
Std. Equipments Mounting	DIN Std. 10mm Square holes OR ETSI Std 10mm Square holes
Standard Finish	Powder coated
Standard Colour	Black
Standard Mounting	Plinth or Casters & Levelers
Rack Standard	DIN 41494 OR equivalent Standard
Static Load	1250 Kg

Accessories :

- Fixed Shelf
- Sliding Shelf
- Shelf/Key Board
- Cantilever Shelf
- Power Distribution Units
- Vertical & Horizontal Cable Organizers
- Grounding and bonding accessories
- Runway & Accessories
- Cable Basket

Abbreviations

H - Overall height
 h - Usable height
 W - Overall width
 w - Usable width
 D - Overall depth
 d - Usable depth

Model Matrix & Dimensions

NRFS Series	H	h	W	w	D	d
44U600X800	2145	44U	600	19"	800	750
44U600X1000	2145	44U	600	19"	800	950

1U = 44.45 mm

Note: Other models can be manufactured on request.

NETRACK™