

Overview

Another challenge in the industry is power loss / shutdown of Mission Critical equipments by accidental Pullover and loose connections in socket & Plug, NetRack offers world class Technology to eliminate this problem once and for all, By IECLock Socket and IECLock Power cord and with combination we can eliminate accidental and vibration disconnects of cable at both PDU and equipment End

Lock Sockets available in C13 and C19 options. NetRack can offer all Socket combination PDU as per NetRack standards or Customer Requirement

Interestingly the IECLock Socket can take Normal Power Cord and with this we can eliminate RISK at PDU side. To eliminate RISK at both PDU & Equipment Side IECLock Socket and IECLock Power Cord Required.



C13 - C14



C19 - C20



C14 - C15

Features - Normal Cables

- Available in 3 Lengths 2, 3, 6 feet
- Cable Available in 7 Colours(on MOQ)
- Readily Available in C13 -14, C14 -15 & C19-20 Configurations
- UL Listed and CE Compliant

Note:

*Standard Length of the cable is 2, 3 & 6 feet other cable lengths are available on MOQ

Model Matrix

Color Description	Part Code
Power Cord/10A/6 Feet/C13-C14/XXXX/CE-UL/18G	PC-10-6-1314-XX-18
Power Cord/16A/6 Feet/C19-C20/XXXX/CE-UL/14G	PC-16-6-1920-XX-14
Power Cord/10A/3 Feet/C13-C14/XXXX/CE-UL/18G	PC-10-3-1314-XX-18
Power Cord/16A/3 Feet/C19-C20/XXXX/CE-UL/14G	PC-16-3-1920-XX-14
Power Cord/10A/2 Feet/C13-C14 /XXXX/CE-UL/18G	PC-10-2-1314-XX-18
Power Cord/16A/2 Feet/C19-C20/XXXX/CE-UL/14G	PC-16-2-1920-XX-14